

# Rack Safety Plus

# Modular Power Distribution Unit with Emergency Stop

# THE FASTEST WAY TO DEVELOP A PDU INCLUDING EMERGENCY SAFETY FUNCTIONS

The nVent SCHROFF Rack Safety Plus PDU with a safety system for installation in a 19" electronics cabinet, is ideal for partially and fully automated test systems. The plug-in unit provides the main power distribution and includes all safety functions according to EN 60947-5-1 and EN 60204. You can choose between several different standard configurations or create your individual configuration by using nVent's online configurator with predefined components.



# **FLEXIBLE**

- · Modular concept with 300K different modification options.
- · Broad experience through customized projects.
- · Include all necessary functions in one system.



# **CERTIFIED**

- · CE and UL certified.
- · Thermal management test and EMC test.
- The safety relay meets the requirements of EN 60947-5-1 and EN 60204-1.



# **READY-TO-USE**

- · Online configurator to modify unit within 5 minutes.
- · Any modification based on the standard platform delivered within 3 weeks.
- · Certified and tested for immediate integration in customer applications.



#### **General Features**

- Form Factor: 3 U, 19" unit, 547,1 mm depth
- Fused power input
- · Main switch
- · ON/OFF switch
- · Emergency stop system
- External emergency status output and connector
- AC outlet plug or outlet plug group
- · Status LED's

## **Possible Configurations**

- Mains Input: 400 V 3-phase or 230 V 1-phase
- · Different connectors
- · EMC filter
- · Different AC Outputs
- · Different DC Output
- · AC Service Outputs
- RCD circuit breaker
- Transparent cover
- · Surge Arrester
- · Inrush Current Limiter
- Different Sizes
- · Remote Management



Item Number	21270-001	21270-003	21270-005
Mains input	3-phase, 400 V AC	1-phase, 230 V AC	1-phase, 230 V AC
Mains connector	IEC 60309 3L+N+PE, 6h	IEC 60320-C20	IEC 60309 L+N+PE, 6h
EMC Filter	Yes	No	No
Surge Arrester	Yes	No	Yes
Inrush Current Limiter	Yes	No	No
RCD	Yes	Yes	Yes
Circuit Breaker Cover	Yes	No	Yes
Service Socket	Front: Schuko Rear: C13	Front: C13	Front: Schuko
AC outlets	12 × C13, 3 × C19	12 × C13, 3 × C19	6 × Schuko
24V DC out	350 W	No	No

Scan the QR code to see other versions.



# PRODUCT CONFIGURATOR

Select the power input, power output, additional features such as a surge arrester or EMC filter based on your infrastructure. Visit: <a href="https://configurators.SCHROFF.biz/rack-safety-plus/eu/en">https://configurators.SCHROFF.biz/rack-safety-plus/eu/en</a>

UK, Ireland

Poland

Italy

Tel +44.144.2218.768

Tel +48.22.209.98.35

Tel +39.02.932.714.1

#### **North America**

## All locations

Tel +1.800.525.4682

## Europe

**Germany** Tel +49.7082.794.0

France Tel +33.388.90.64.90

Sweden, Norway, Finland

Tel +46.8.683.61.00

# Asia/Pacific

## **VR** China

Tel +86.21.2412.6943 Singapore

Tel +65.6768.5800 **Japan** 

Tel +81.45.476.0271

## Middle East & India

United Arab Emirates Tel +971.4.823.8666

India

Tel +91.80.6715.8900 **Turkey** 

Tel +90.541.3680941

nVent com/CCUDOEE | 2



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE

©2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without notice.